

# COR-SP600

## HIGH DEFINITION 12X ZOOM SPEED DOME w/ WDR



### FEATURES

- 360° ENDLESS ROTATION
- VECTOR DRIVE
- COMPOUND MOVEMENT
- PATTERN RECORDING
- 12 X OPTICAL ZOOM



12 X  
OPTICAL  
ZOOM



### SPECIFICATIONS

GENERAL	
Sensor	1/4"Sony Super HAD II CCD
Color System	NTSC
Resolution	700 TVL
S/N	50 dB (AGC Off)
Mini Illumination	0.5 lux B/W : 0.2 lux Color DSS : 0.001 lux B/W DSS : 0.0004 lux
Day/Night	Auto/Day/Night
WDR	On/Off
DIS	On/Off
DSS	2x-512x
DNR	On/Off
AGC	Auto / Manual
White Balance	Auto WB /Outdoor / Indoor/One Push WB / Manual WB
BLC/HLC	On/Off
Flickerless	On/Off
Brightness	Adjustable (0-96)
Pan/Tilt Range	Horizontal: 360 °(Endless) / Vertical: 90
Speed	Preset : 360 ° / sec. Manual : 0 ~ 360 ° / sec. (proportional to zoom ratio)
Preset	127
Auto Scan	8
Pattern	4
Group	8
Other functions	Auto Flip, Park Position, Power Up
Communication	RS-485
Protocol	Pelco-D -Pelco-P
Privacy zone	8 zones could be programmed
Alarm	I/O, 2CH Input / 1CH Output

### FULL LINE OF ACCESSORIES




COR-SP6BPE



COR-SP6BWC



COR-SP6BC



COR-SP6BH

### TEMPERATURE / HUMIDITY

Working Temp	-30°C~ 50°C
Fan/Heater Start Temp.	Fan start temp.:25°C ; Heater start temp.°5C
Working Humidity	0%~90% (Non-condensation)

### LENS

Focal Length	f-3.8 (Wide) – 45.6 (Tele)mm
Zoom Ratio	12x Optical zoom 32x digital zoom
View Angle	2.8°(W) ~ 4.49°(T)
Iris	F1.6 (Wide)-F2.7 (Tele) Color
Iris Adjustment	Auto/Manual
Focus	Auto/Manual/Semi-Auto
Shutter Speed	Auto(x128 ~ 1/60 sec. ~ 1/10000 sec.)

### WEIGHT AND DIMENSIONS

Weight	1.9 (kg) 4.3 (lb) (Indoor); 2.5 (kg) 5.5 (lb) (Outdoor)
Height & Width	165mm x157.5 (mm) 6.5" x 6.2" (Indoor) 199.3mmx183.6(mm) 7.8"x 7.2"(Outdoor)

### POWER

Max. Power Consumption	Fan On:10W :Heater On:21W (Outdoor)
Input Voltage	12VDC/24VAC

COR-SP600

