

COR-SP650E

HIGH DEFINITION 36X OPTICAL ZOOM SPEED DOME w/ WDR



FEATURES

- 360° ENDLESS ROTATION
- VECTOR DRIVE
- COMPOUND MOVEMENT
- PATTERN RECORDING
- 36 X OPTICAL ZOOM




36 X
OPTICAL
ZOOM

SPECIFICATIONS

GENERAL	
Sensor	1/4" Sony Super HAD II CCD
Color System	NTSC
Resolution	700 TVL
Signal to Noise Ratio	50 dB (AGC Off)
Min. Illumination	Color : 0.5 lux - B/W : 0.2 lux Color DSS : 0.001 lux -
Day/Night	Auto/Day/Night
WDR	On/Off
DIS	On/Off
DSS	2x-512x
DNR	On/Off
AGC	Auto / Manual
White Balance	Auto WB / Outdoor / Indoor/One Push WB / Manual WB
BLC/HLC	On/Off
Flickerless	On/Off
Brightness	Adjustable (0-96)
Pan/Tilt Range	Horizontal: 360 °(Endless) / Vertical: 90
Speed	Preset : 400 °/sec. Manual : 0 ~ 360 °/ sec. (proportional to zoom ratio)
Preset	127
Auto Scan	8
Pattern	4
Group	8
Alarm I/O	8CH Input / 4CH Output
Other functions	Auto Flip, Park Position, Power Up
Communication	RS-485
Protocol	Pelco-D -Pelco-P
Privacy zone	8 zones could be programmed
Working Temp	-30°C ~ 50 °C

FULL LINE OF ACCESSORIES



COR-SP6BH



COR-SP6BPE



COR-SP6BWC

LENS	
Focal Length	f=3.4 (Wide) - 122.4 (Tele)mm
Zoom Ratio	36x Optical zoom -32x digital zoom
View Angle	57.8°(W) ~ 1.7°(T)
Iris	F1.6 (Wide)-F4.5 (Tele)
Iris Adjustment	Auto/Manual
Focus	Auto/Manual/Semi-Auto
Shutter Speed	Auto(x128 ~ 1/60 sec. ~ 1/10000 sec.)
WEIGHT AND DIMENSIONS	
Weight	5 (kg) 11 (pounds)
Height & Width	289 x 228 (mm) 11.4" x 9" (inches) Not including Bracket
POWER	
Max. Power Consumption	44W (Outdoor) 24W (Indoor)
Input Voltage	12VDC/24VAC

COR-SP650E

