

# COR-ACC890

## OUTDOOR QUICKPASS PROXIMITY CARD READER

Includes electric door relay  
COR-ACC899



0.75"



Threaded Security  
Screw Port

Keypad Port



2"

### SPECIFICATIONS

Operating modes	Standalone or connect to COR-ACC1000
Control mode	Card capacity and card type assignable
Card Reader Range	10 - 18cm (125kHz)
Communication	RS485
Baud rate	9600 bps (N.,8,1)
Time zone	11. user defined in client software
Holiday scheduling	User defined in client software
Users	1024 in networking mode, 65535 in standalone mode
Auxiliary WG port	WG 26/34, ABA II
Auto open door zones	Two (programmable)
Door relay time	0, 0.1-600 sec
Alarm relay time	0, 0.1-600 sec
Tamper resistance	Limit switch (Form C)
Serial out	TTL (4800 bps, N, 8,1 )
Real time clock	Yes
Indicators	One two-color LED, One beeper
Power	12VDC
Construction	Hardened zinc-alloy
Dimensions	160mm (H) 50.8mm (W) 19.05mm (D) 6.125inches (H) 2inches (W) .75 inches (D)
Weight	290g (10.23oz)
Operating temperature	-20°C to +75°C (-4°F to +167°F)
Weatherproof rating	IP54, good for indor or outdoor placement

6.125"



COR-ACC890

