

## Nubix 8RT



## PC/MAC Compatible Real Time Security

Real time recording, PC and MAC connectivity and fast remote viewing using iPhone or Android (3G/4G networks) define the Nubix RT series.



- → DOWNLOAD YOUR OWN ADVERTISEMENTS to the built-in media center from USB stick, remove USB stick for added security.
- FLEXIBLE SPOT/MAIN MONITOR selection (select VGA or composite).
- DUAL STREAMING record in D1 resolution and stream to cell phone in CIF resolution to conserve bandwidth.
- REAL TIME recording on all 8 channels simultaneously.
- → Simultaneous synchronous 8 channel playback with audio.
- Built-in Point-of-Sale (POS) functions with searchable text.
- Intuitive, easy to understand menus make it easy to program for you and your clients!

## FREE 64 Camera Channel Management System




Free CMS software included with every Nubix RT DVR lets you connect to up to 128 cameras remotely, program your DVR and set up special features like 2–way audio communication.

FREE IR Remote Control



Optional video loop-out connectors available









## **General Specifications**

Video Compression: H264 advanced video codec

Video Input: 8 channels, BNC connectors

Record speed/resolution: 240 ips (images per second) CIF (NTSC)

120 ips 1/2 D1 (NTSC) 60 ips D1 (NTSC)

Record Quality Settings: Very High, High, Standard, Low

Recording Modes: Time-lapse, Event, Time & Event, Panic

Video Playback Modes: Single camera, Four camera split screen,

Digital zoom, Multi-channel normal & reverse play, RW, FF, Frame-to-frame,

Pause

Video Search Modes: Calendar, Event, Text-in, Go to time

Rewind & Fast Forward Speeds: x2, x4, x8, x16, x32

Spot & Main Monitor Outputs: 1 VGA & 1 composite (BNC)

Display Speed: Real Time

Display Resolution: 720 x 480 (NTSC)

Split Screen Options: 1, 4, 9, PIP & Digital Zoom

Audio Input: 8

Audio Outputs: 1

Sensor Inputs: 8 (TTL)

Alarm Outputs: 4 TTL & 4 Relay

Serial Interface: RS232 and RS485

PTZ Support: Yes, RS485

USB: 3 USB 2.0 ports

Mouse: 1 dedicated USB port

Network Interface: Ethernet 10/100 base

Network Protocol: TCP/IP, HTTP, DHCP

Web Browser: MS Internet Explorer

Storage: 2 SATA devices

Backup: Optional CD & DVD R/W, USB device (HDD or Flash

Memory)

User Controls: IR Remote Control, Mouse or Front panel buttons

Programming/Setup Menu: Multilingual On-screen display (OSD)

Operating System: Multilingual Linux GUI (upgradeable)

Power: 12VDC, 6.67A (80W) nominal

Weight: 13lb (6Kg) w/o HDD

Dimensions: 16.93"(w) x 3.5"(h) x 16.85"(d)

430mm(w) x 88mm(h) x 428mm(d)

Operating Temperature: 41° ~ 104°F (5° ~ 40°C)

Operating Humidity: 0% ~ 80% non-condensing

Approvals/Certifications: FCC, CE, MIC, RoHS compliance

Auto-Archiving Feature: Yes