

# COR-IP2SPD

## 2MP NETWORK PTZ CAMERA with 22 x OPTICAL ZOOM



### FEATURES

- 1/2.8" Progressive CMOS
- 22 x optical zoom
- Infrared dimming function
- 360°endless rotation
- IR Range up to 500 feet
- Metal Housing IP66 Waterproof
- 1920(H)×1080(V) Resolution



### SPECIFICATIONS

| CAMERA*              |                                                       |
|----------------------|-------------------------------------------------------|
| Image Sensor         | 1/2.8" Progressive Scan CMOS                          |
| Effective Pixels     | 1920x1080                                             |
| Signal System:       | PAL / NTSC                                            |
| Lens                 | 22X Optical Zoom                                      |
| Focal Length         | F1.6 ~ F3.0 , 4.7mm -104mm                            |
| Angle of View        | 72~ 3.8 degree (Wide~Tele)                            |
| Minimum Illumination | AGC On: Color: 0.5 lux, B/W : 0.05 lux, 0 lux with IR |
| White Balance        | Auto/Manual/Indoor                                    |
| AGC                  | Auto/Manual                                           |
| BLC                  | ON/OFF                                                |
| Smart defog          | Support                                               |
| WDR                  | 120 dB                                                |
| Shutter Time         | 1/5 - 1/20000                                         |
| SD Card              | Internal                                              |
| Day & Night          | IR cut filter with auto switch                        |
| VIDEO*               |                                                       |
| Compression          | Main Stream : H.265 / H.264                           |
| Video Output         | 1 Output : CVBS(BNC Type)                             |
| Transmission         | H.265 / H.264 Triple Streaming                        |
| Resolution           | 30fps@1920*1080 ~ 30fps@320*240                       |
| AUDIO*               |                                                       |
| Input                | 1 Line-in                                             |
| Output               | 1 Line-out                                            |
| ALARM*               |                                                       |
| Input                | 1 inputs                                              |
| Output               | 1 output                                              |

| NETWORK*                      |                                                                          |
|-------------------------------|--------------------------------------------------------------------------|
| Ethernet                      | 10/100Mbps ethernet interface                                            |
| Protocols                     | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,   |
| No. of Simultaneous Users     | 5 users                                                                  |
| RS485 interface               | Control by Joystick controller(Only used PTZ function)                   |
| INFRARED*                     |                                                                          |
| IR irradiation distance       | 500 feet (150m)                                                          |
| IR Diming function            | Adjustable by zoom                                                       |
| PAN & TILT                    |                                                                          |
| Pan Range                     | 360°endless                                                              |
| Tilt Range                    | -10°~95° (Auto Flip )                                                    |
| Pan Speed                     | 0.1~300°/sec                                                             |
| Tilt Speed                    | 0.1~100°/sec                                                             |
| Proportional Zoom             | Rotation speed can be adjusted automatically according to zoom multiples |
| Preset                        | 255                                                                      |
| Preset Speed                  | Max.300°/sec                                                             |
| Tour                          | 4 Tours/8 preset each                                                    |
| Pattern                       | 4 Patterns                                                               |
| Scan                          | 1 Scans                                                                  |
| Home position                 | Preset / Tour / Scan / Pattern                                           |
| GENERAL*                      |                                                                          |
| Water Proof                   | IP66                                                                     |
| Power Supply                  | AC 24V/DC 12V                                                            |
| Working Temperature/Humidity: | -10°C~-60°C,<90%(outdoor)                                                |
| Dimensions                    | 351.8 x 206.44 mm<br>13.8 ix 8.1 inches                                  |
| Weight                        | Approx. 6.6 pounds 2kg                                                   |

COR-IP2SPD



©2020 Cortex®  
As our product is subject to continuous improvement, Cortex & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE.  
Distributed by www.cortexcctv.com 01-01022020