

COR-IP5SPD20

5MP IP PTZ 20 x ZOOM with 450 FOOT IR RANGE



KEY FEATURES

- 1/3" CMOS
- 5MP 2592 x 1944
- 4.7mm - 94mm 20 x zoom lens
- Supports P2P, Android, ISO
- Digital WDR
- H.264 / H.265 Video Compression
- IR range 450 feet
- 360° continued rotation



20X
OPTICAL
ZOOM



SPECIFICATIONS

* CAMERA	
Image Sensor	1/3" 5.0M Pixel CMOS
Effective Pixels	5.0 Megapixels
Min. Illumination	Color: 0.05Lux@ (F1.6, AGC ON) ; 0.01Lux@ (F1.6, AGC ON)
Zoom	20X , f=4.7mm~94mm, D/N (ICR-Cut) , F1.6~F3.0
Day / Night	Day / Night / External control (IR Cut Filter)
SNR	≥50dB (AGC OFF)
WDR	Digital WDR, ≥87. 5dB 0.05 lux, 0 lux with IR
White balance	Auto / Manual / ATW / Indoor/ Outdoor Daylight lamp / Sodium lamp
AGC	Auto / Manual
DNR	DNR,3DNR
Shutter speed	1/2 - 1/20,000s
WDR	120db
Shutter time	1/5 - 1/20000
* VIDEO	
Video Compression	H.265 Main Profile / H.264 Main Profile / M-JPEG
Streams	Triple streams
Bitrate	CBR / VBR, bitrate:32Kbps~10Mbps
Resolution	30fps@ 1920*1080 ~ 30fps@ 320*240
* AUDIO	
Audio Compression	G711, PCM
Audio I/O	1 input (Linear level, Resistance: 1000 Ohm); 1 output (Linear level, Resistance: 600 Ohm);
* NETWORK	
Frame Rate	Main stream: 2592x1944/15fps 2592x1520 / 25fps Sub-stream: 480*640, 1-25(30)fps; 480 *3601-25(30)fps 352*288, 1-25(30)fps; 176*1441-25(30)fps 480*640, 1-25(30)fps 480*3601-25(30)fps 352*288, 1-25(30)fps; 176*144, 1-25(30)fps 480 *360 1-25(30)fps 480*640, 1-25(30)fps; 480 *360 1-25(30)fps 352*288, 1-25(30)fps; 176*144, 1-25(30)fps MJPEG: 1920*1080, 1280*720, Close

* NETWORK	
Protocols	TCP/IP/ HTTP/NTP/ IGMP/ DHCP/ UDP/ SMTP/ RTP/ RTSP/ ARP /DDNS /DNS/ P2P
Onvif ®	Onvif ® 2.4
Network	10/100M Base-TX Ethernet, RJ45 Connector
Supports	P2P , Android, IOS
* INFRARED	
Luminary	Array Φ20 6pcs
Night vision distance	450 (feet) 137.16 (meters)
Lamp control	Auto, Manual, by Zoom
* DOME FEATURES	
CPU Type	32 bit ARM CPU
Address	0~255 (soft address and hard address)
Pan Range	360° continued rotation
Tilt Range	0~90°(Auto Flip)
Manual pan speed	0.01~200° /S, 0.01~200°/S
Manual tilt speed	0.01~120°/S
Preset speed	400°/S
Actual preset Accuracy	±0.10°
Preset points	255
Other function	5Tour, Intelligent Three dimensional Scan, 1Pattern group ,Operation recall, Manual continued Auto Scan
Intelligent power off real time memory	Automatic save functions setting ,automatic wake up tour function
Motion detect	Support
Privacy Zone Masking	Support
Mini SD Card	Up to 64GB (Optional)
* GENERAL	
Power	DC12V±10%; 5A/ PoE++
Working Temperature/ Humidity	-35°C ~ + 55°C (-31~+131°F) <90% (Non condensing)
Consumption	< 50W
Dimensions	370 x 227 mm 14.5 ix 8.9 inches

COR-IP5SPD20

