

COR-IP5SPD30

5MP IP PTZ 30 x ZOOM with 984 FOOT IR RANGE



KEY FEATURES

- 1/2.8.5" Sony® CMOS
- 5MP 2592 x 1944
- 4.7mm - 94mm 30 x zoom lens
- Supports P2P, Android, ISO
- Digital WDR
- H.265 Video Compression
- IR range 984 feet
- 360° continued rotation



30X
OPTICAL
ZOOM



SPECIFICATIONS

* CAMERA	
Image Sensor	1/2.8" 5.0M Pixel Sony® IMX335 CMOS
Effective Pixels	5.0 Megapixels
Min. Illumination	Color; 0.02Lux@(F1.6, AGC ON) ; 0.01Lux@(F1.6, AGC ON)
Zoom	30X , f=4.7mm~94mm, D/N(ICR-Cut) ,F1.6~F3.0
Day / Night	Day / Night / External control (IR Cut Filter)
SNR	≥50dB (AGC OFF)
WDR	Digital WDR ,≥87.5dB
White balance	Auto / Manual / ATW / Indoor/ Outdoor Daylight lamp / Sodium lamp
AGC	Auto / Manual
DNR	DNR,3DNR
Shutter speed	1/2 - 1/20,000s
* VIDEO	
Video Compression	H.265 Main Profile / H.264 Main Profile / M-JPEG
Streams	Triple streams
Bitrate	CBR / VBR, bitrate:32Kbps~10Mbps
* AUDIO	
Audio Compression	G711, PCM
Audio I/O	1 input (Linear level, Resistance: 1000 Ohm); 1 output (Linear level, Resistance: 600 Ohm);
* NETWORK	
Frame Rate	Main stream: 2592x1944/15fps 2592x1520 / 25fps Sub-stream: 480*640, 1-25(30)fps; 480 *360 1-25(30)fps 352*288, 1-25(30)fps; 176*144, 1-25(30)fps MJPEG: 1920*1080, 1280*720, Close

* NETWORK	
Protocols	TCP/IP/ HTTP/NTP/ IGMP/ DHCP/ UDP/ SMTP/ RTP/ RTSP/ ARP /DDNS /DNS/ P2P
Onvif ®	Onvif ® 2.4
Network	10/100M Base-TX Ethernet, RJ45 Connector
P2P	Android, IOS
* INFRARED	
Luminary	Array Φ20 8pcs
Night vision distance	984(feet) 300 (meters)
Lamp control	Auto, Manual, by Zoom
* DOME FEATURES	
CPU Type	32 bit ARM CPU
Address	0~255 (soft address and hard address)
Pan Range	360° continued rotation
Tilt Range	0~90°(Auto Flip)
Manual pan speed	0.01~60°/S
Manual tilt speed	0.01~60°/S
Preset speed	200°/S
Actual preset Accuracy	±0.10°
Preset points	255
Other function	5Tour, Intelligent Three dimensional Scan, 1Pat-tern group ,Operation recall, Manual continued Auto Scan
Intelligent power off real time memory	Automatic save functions setting ,automatic wake up tour function
Motion detect	Support
Privacy Zone Masking	Support
Mini SD Card	Up to 64GB (Optional)
* GENERAL	
Power	DC12V±10%; 5A
Working Temperature	External -35°C ~ + 55°C (-31~+131°F)
Working Humidity	0%~90% (Non condensing)
Consumption	< 50W
Dimensions	370 x 227 mm 14.5 ix 8.9 inches

COR-IP5SPD30

